

Manual

GAUSSRATE – version 9.1

Jose C. Corchado, Yao-Yuan Chuang, Elena L. Coitiño, and Donald G. Truhlar
Department of Chemistry and Supercomputer Institute
University of Minnesota, Minneapolis, Minnesota 55455

Program version: 9.1/P9.1-G03G98G94
Program version date: July 7, 2003
Manual version date: July 7, 2003
Copyright 2003

Abstract:

GAUSSRATE is a set of FORTRAN subroutines and Unix scripts for interfacing the POLYRATE and GAUSSIAN 03 (or 98 or 94) computer programs for the purpose of carrying out direct dynamics calculations of gas-phase chemical reaction rates of polyatomic species (and also atoms and diatoms as special cases) using the electronic structure methods available in GAUSSIAN 03 (or 98 or 94) to calculate the potential energy surface and POLYRATE for the dynamics. The interface is based on the POLYRATE hooks protocol. The dynamical methods used are variational or conventional transition state theory and multidimensional semiclassical approximations for tunneling and nonclassical reflection. Rate constants may be calculated by any of the methods available in the POLYRATE–version 9.1 program for canonical or microcanonical ensembles or for specific vibrational states of selected modes with translational, rotational, and other vibrational modes treated thermally. Bimolecular and unimolecular reactions are included. Both single-level and dual-level calculations may be carried out. In single-level mode, optimized geometries, potential energies, gradients, and Hessians can be calculated by any of the ab initio or semiempirical methods in the GAUSSIAN 03 (or 98 or 94) packages. In dual-level mode, the lower-level data is calculated by GAUSSIAN 03 (or 98 or 94), and the higher-level data is read in from an external file.

GAUSSRATE–version 9.1 provides an interface between two other programs:

POLYRATE–version 9.1, by J. C. Corchado, Y. -Y. Chuang, P. L. Fast, J. Villa, W. -P. Hu, Y. -P. Liu, G. C. Lynch, K. A. Nguyen, C. F. Jackels, V. S. Melissas, B. J. Lynch, I. Rossi, E. L. Coitiño, A. Fernandez-Ramos, J. Pu, T. V. Albu, R. Steckler, B. C. Garrett, A. D. Isaacson, and D. G. Truhlar, University of Minnesota, Minneapolis, MN, 2003.

and

GAUSSIAN 03, by M. J. Frisch, G. W. Trucks, H. B. Schlegel, G. E. Scuseria, M. A. Robb, J. R. Cheeseman, J. A. Montgomery, Jr., T. Vreven, K. N. Kudin, J. C. Burant, J. M. Millam, S. S. Iyengar, J. Tomasi, V. Barone, B. Mennucci, M. Cossi, G. Scalmani, N. Rega, G. A. Petersson, H. Nakatsuji, M. Hada, M. Ehara, K. Toyota, R. Fukuda, J. Hasegawa, M. Ishida, T. Nakajima, Y. Honda, O. Kitao, H. Nakai, M. Klene, X. Li, J. E. Knox, H. P. Hratchian, J. B. Cross, C. Adamo, J. Jaramillo, R. Gomperts, R. E. Stratmann, O. Yazyev, A. J. Austin, R. Cammi, C. Pomelli, J. W. Ochterski, P. Y. Ayala, K. Morokuma, G. A. Voth, P. Salvador, J. J. Dannenberg, V. G. Zakrzewski, S. Dapprich, A. D. Daniels, M. C. Strain, O. Farkas, D. K. Malick, A. D. Rabuck, K. Raghavachari, J. B. Foresman, J. V. Ortiz, Q. Cui, A. G. Baboul, S. Clifford, J. Cioslowski, B. B. Stefanov, G. Liu, A. Liashenko, P. Piskorz, I. Komaromi, R. L. Martin, D. J. Fox, T. Keith, M. A. Al-Laham, C. Y. Peng, A. Nanayakkara, M. Challacombe, P. M. W. Gill, B. Johnson, W. Chen, M. W. Wong, C. Gonzalez, and J. A. Pople, Gaussian, Inc., Pittsburgh PA, 2003.

or

GAUSSIAN 98, by M. J. Frisch, G. W. Trucks, H. B. Schlegel, G. E. Scuseria, M. A. Robb, J. R. Cheeseman, V. G. Zakrzewski, J. A. Montgomery, R. E. Stratmann, J. C. Burant, S. Dapprich, J. M. Millam, A. D. Daniels, K. N. Kudin, M. C. Strain, O. Farkas, J. Tomasi, V. Barone, M. Cossi, R. Cammi, B. Mennucci, C. Pomelli, C. Adamos, S. Clifford, J. Ochterski, G. A. Petersson, P. Y. Ayala, Q. Cui, K. Morokuma, D. K. Malick, A. D. Rabuck, K. Raghavachari, J. B. Foresman, J. Cioslowski, J. V. Ortiz, B. B. Stefanov, G. Liu, A. Liashenko, P. Piskorz, I. Komaromi, R. Gomperts, R. L. Martin, D. J. Fox, T. Keith, M. A. Al-Laham, C. Y. Peng, A. Nanayakkara, C. Gonzalez, M. Challacombe, P. M. W. Gill, B. G. Johnson, W. Chen, M. W. Wong, J. L. Andres, M. Head-Gordon, E. S. Replogle and J. A. Pople, Gaussian, Inc., Pittsburgh PA, 1999.

or

GAUSSIAN 94, by M. J. Frisch, G. W. Trucks, H. B. Schlegel, P. M. W. Gill, B. G. Johnson, M. A. Robb, J. R. Cheeseman, T. Keith, G. A. Petersson, J. A. Montgomery, K. Raghavachari, M. A. Al-Laham, V. G. Zakrzewski, J. V. Ortiz, J. B. Foresman, J. Cioslowski, B. B. Stefanov, A. Nanayakkara, M. Challacombe, C. Y. Peng, P. Y. Ayala, W. Chen, M. W. Wong, J. L. Andres, E. S. Replogle, R. Gomperts, R. L. Martin, D. J. Fox, J. S. Binkley, D. J. Defrees, J. Baker, J. P. Stewart, M. Head-Gordon, C. Gonzalez, and J. A. Pople, Gaussian, Inc., Pittsburgh PA, 1995.

CONTENTS

| | |
|---|----|
| TITLE PAGE AND ABSTRACT | 1 |
| CONTENTS | 3 |
| 1. USER AGREEMENT | 4 |
| 2. REQUIRED REFERENCES | 5 |
| 3. INTRODUCTION | 7 |
| 4. DISTRIBUTION | 9 |
| 5. INSTALLATION | 12 |
| 6. PROGRAM DESCRIPTION | 14 |
| 6.1. Description of GAUSSRATE subprograms | 14 |
| 6.2. Restarting a calculation | 17 |
| 7. DESCRIPTION OF INPUT FILES | 20 |
| 7.1. File usage | 20 |
| 7.2. Description of fu5 unit | 22 |
| 7.3. Description of esp.fu71 through esp.fu78 input files | 28 |
| 7.4. Description of esp.fu70 input file | 30 |
| 7.4.1. The GRGENERAL section | 31 |
| 7.4.2. The GRCOMMON section | 32 |
| 7.4.3. The GRREACT1, GRREACT2, GRPROD1, GRPROD2, GRWELLR, GRWELLP, GRSTART, and GRPATH sections . | 35 |
| 8. TESTING GAUSSRATE | 37 |
| 8.1. Tests performed | 37 |
| 8.2. Test suite | 38 |
| 8.2.1. Test run ch5tr1 | 39 |
| 8.2.2. Test run ch5tr2 | 40 |
| 8.2.3. Test run oh3tr1 | 41 |
| 8.2.4. Test run oh3tr2 | 42 |
| 8.2.5. Test run oh3tr3 | 43 |
| 8.2.6. Test run ch4ohtr1 | 44 |
| 8.2.7. Test run ch4ohtr2 | 45 |
| 8.2.8. Test run ch4ohtr3 | 46 |
| 8.2.9. Test run ch4ohtr4 | 47 |
| 8.2.10. Test run ch4ohtr5 | 49 |
| 8.2.11. Test run ch4ohtr6 | 51 |
| 8.2.12. Test run nh3ohtr1 | 52 |
| 8.3. Test run timings | 53 |
| 9. COMPUTERS, OPERATING SYSTEMS, AND GAUSSIAN VERSIONS ON WHICH THE CODE HAS BEEN DEVELOPED AND TESTED | 54 |
| 10. VERSION INFORMATION | 56 |
| 11.1. GAUSSRATE version numbers | 56 |
| 11.2. GAUSSRATE revision history | 57 |
| 11. ACKNOWLEDGMENTS | 64 |

1. USER AGREEMENT

GAUSSRATE is a licensed program, and the use of this program implies acceptance of the terms of the license, which are repeated here for convenience:

- A. No user or site will redistribute the source code or executable code to a third party in original or modified form without written permission of the principal investigator (Donald G. Truhlar). A license does not entitle the licensee to relicense the code or distribute it in original or modified form to parties not covered by the license. The licensee has no ownership rights in the GAUSSRATE software or in any copyrights for the GAUSSRATE software or documentation through this license. A user license covers the work of a single research group and the code may be shared and disseminated within a group without requiring permission. Site-license inquiries should be directed to the principal investigator (Donald G. Truhlar).
- B. Publications resulting from using this package or the POLYRATE or GAUSSIAN subsystems used by this package will cite the corresponding program. The required references are given in the documentation (see Section 2 for the required references for GAUSSRATE).
- C. No guarantee is made that this program is bug-free or suitable for specific applications, and no liability is accepted for any limitations in the mathematical methods and algorithms used within the program.
- D. No consulting or maintenance services are guaranteed or implied.
- E. The POLYRATE 9.1, and GAUSSIAN 03, or GAUSSIAN 98, or GAUSSIAN 94 codes, required to use GAUSSRATE, are covered by separate licenses.

2. REQUIRED REFERENCES

Publications based on results obtained with this computer code should include the following references:

1. J. C. Corchado, Y.-Y. Chuang, E. L. Coitiño, and D. G. Truhlar, GAUSSRATE—version 9.1, University of Minnesota, Minneapolis, MN, 2003.
2. J. C. Corchado, Y.-Y. Chuang, P. L. Fast, J. Villa, W.-P. Hu, Y.-P. Liu, G. C. Lynch, K. A. Nguyen, C. F. Jackels, V. S. Melissas, B. J. Lynch, I. Rossi, E. L. Coitiño, A. Fernandez-Ramos, J. Pu, T. V. Albu, R. Steckler, B. C. Garrett, A. D. Isaacson, and D. G. Truhlar, POLYRATE—version 9.1, University of Minnesota, Minneapolis, MN, 2002.

and

- 3A. M. J. Frisch, G. W. Trucks, H. B. Schlegel, G. E. Scuseria, M. A. Robb, J. R. Cheeseman, J. A. Montgomery, Jr., T. Vreven, K. N. Kudin, J. C. Burant, J. M. Millam, S. S. Iyengar, J. Tomasi, V. Barone, B. Mennucci, M. Cossi, G. Scalmani, N. Rega, G. A. Petersson, H. Nakatsuji, M. Hada, M. Ehara, K. Toyota, R. Fukuda, J. Hasegawa, M. Ishida, T. Nakajima, Y. Honda, O. Kitao, H. Nakai, M. Klene, X. Li, J. E. Knox, H. P. Hratchian, J. B. Cross, C. Adamo, J. Jaramillo, R. Gomperts, R. E. Stratmann, O. Yazyev, A. J. Austin, R. Cammi, C. Pomelli, J. W. Ochterski, P. Y. Ayala, K. Morokuma, G. A. Voth, P. Salvador, J. J. Dannenberg, V. G. Zakrzewski, S. Dapprich, A. D. Daniels, M. C. Strain, O. Farkas, D. K. Malick, A. D. Rabuck, K. Raghavachari, J. B. Foresman, J. V. Ortiz, Q. Cui, A. G. Baboul, S. Clifford, J. Cioslowski, B. B. Stefanov, G. Liu, A. Liashenko, P. Piskorz, I. Komaromi, R. L. Martin, D. J. Fox, T. Keith, M. A. Al-Laham, C. Y. Peng, A. Nanayakkara, M. Challacombe, P. M. W. Gill, B. Johnson, W. Chen, M. W. Wong, C. Gonzalez, and J. A. Pople, GAUSSIAN 03, Gaussian, Inc., Pittsburgh, PA, 2003.

or

- 3B. M. J. Frisch, G. W. Trucks, H. B. Schlegel, G. E. Scuseria, M. A. Robb, J. R. Cheeseman, V. G. Zakrzewski, J. A. Montgomery, Jr., R. E. Stratmann, J. C. Burant, S. Dapprich, J. M. Millam, A. D. Daniels, K. N. Kudin, M. C. Strain, O.

Farkas, J. Tomasi, V. Barone, M. Cossi, R. Cammi, B. Mennucci, C. Pomelli, C. Adamo, S. Clifford, J. Ochterski, G. A. Petersson, P. Y. Ayala, Q. Cui, K. Morokuma, P. Salvador, J. J. Dannenberg, D. K. Malick, A. D. Rabuck, K. Raghavachari, J. B. Foresman, J. Cioslowski, J. V. Ortiz, A. G. Baboul, B. B. Stefanov, G. Liu, A. Liashenko, P. Piskorz, I. Komaromi, R. Gomperts, R. L. Martin, D. J. Fox, T. Keith, M. A. Al-Laham, C. Y. Peng, A. Nanayakkara, M. Challacombe, P. M. W. Gill, B. Johnson, W. Chen, M. W. Wong, J. L. Andres, C. Gonzalez, M. Head-Gordon, E. S. Replogle, and J. A. Pople, GAUSSIAN 98, Gaussian, Inc., Pittsburgh, PA, 2001.

or

- 3C. M. J. Frisch, G. W. Trucks, H. B. Schlegel, P. M. W. Gill, B. G. Johnson, M. A. Robb, J. R. Cheeseman, T. Keith, G. A. Petersson, J. A. Montgomery, K. Raghavachari, M. A. Al-Laham, V. G. Zakrzewski, J. V. Ortiz, J. B. Foresman, J. Cioslowski, B. B. Stefanov, A. Nanayakkara, M. Challacombe, C. Y. Peng, P. Y. Ayala, W. Chen, M. W. Wong, J. L. Andres, E. S. Replogle, R. Gomperts, R. L. Martin, D. J. Fox, J. S. Binkley, D. J. Defrees, J. Baker, J. P. P. Stewart, M. Head-Gordon, C. Gonzalez, and J. A. Pople, GAUSSIAN 94, Gaussian Inc., Pittsburgh, 1995.

Additional references are given in the documentation for POLYRATE and GAUSSIAN.

3. INTRODUCTION

GAUSSRATE is a program for the analysis of reactants, products, and transition states of chemical reactions and for direct dynamics calculations of variational transition state theory (VTST) rate constants and multi-dimensional semiclassical tunneling probabilities using the electronic structure methods in the GAUSSIAN 03 (or 98 or 94) packages to represent the potential energy of interaction and its first and second derivatives whenever they are needed. This version, 9.1/P9.1-G03G98G94, interfaces POLYRATE-version 9.1, which is a program for dynamical rate calculations, with the electronic structure program GAUSSIAN 03 (or 98 or 94).

Using GAUSSRATE presuppose that the user has both POLYRATE 9.1 and GAUSSIAN 03 (or 98 or 94) on the same computer working properly before attempting to run GAUSSRATE. No part of POLYRATE 9.1 or GAUSSIAN 03 (or 98 or 94) is contained in GAUSSRATE or needs to be modified for running this program.

This GAUSSRATE manual covers only material that is not covered in the POLYRATE and GAUSSIAN 03 (or 98 or 94) manuals. The user of GAUSSRATE should read those manuals first.

The interface between POLYRATE and GAUSSIAN 03 (or 98 or 94) is made by a series of FORTRAN subroutines included in the files `hooks_gr.f` and `hooks_mdep.f`, which are specialized versions of the routines in the `hooks.f` file in POLYRATE 9.1 and by a C shell script for running GAUSSIAN 03 (or 98 or 94). This C shell script, named `shuttle`, is called from inside GAUSSRATE, and it has to be able to start running GAUSSIAN 03 (or 98 or 94) using an input file named as the first argument given to `shuttle`. It produces an output file named as the second argument given to `shuttle`. For the user's convenience, a well documented script is provided, and in most cases the user will only need to change one line, in order to set the *gausspath* variable to the appropriate path where GAUSSIAN 03 (or 98 or 94) is located. In the provided script, the variable *scratchdir*, which indicates the directory where the temporary and scratch GAUSSIAN 03 (or 98 or 94) files are going to be located, is set to the working directory; if desired, the user can change this. In some systems, the `g03.login` (or `g98.login` or `g94.login`) files have to be loaded previously to any GAUSSIAN 03 (or 98 or 94) calculations. In such a case, the user should uncomment the line in the `shuttle` script

that loads it or contact the system manager in order to get instructions about how to load this file.

Note that running two GAUSSRATE calculations or a GAUSSIAN and a GAUSSRATE calculation in the same directory can cause problems due to overwriting of some of the temporary files.

GAUSSRATE uses a subroutine usually included in libraries provided with FORTRAN compilers. This subroutine is called *system* on the IBM RS/6000, Silicon Graphics IRIS-Power Challenge, and Sun computers. (The subroutine is called *ishell* on the Cray C90 supercomputer.) The prospective user of GAUSSRATE should be aware that this utility program is needed for running GAUSSRATE.

4. DISTRIBUTION

GAUSSRATE is a set of subroutines for interfacing POLYRATE and GAUSSIAN. The user needs to obtain four items of code:

- POLYRATE: The POLYRATE code is a licensed code available from the University of Minnesota. Currently the license fee is waived for all users. For further information see:
<http://comp.chem.umn.edu/polyrate>
- GAUSSIAN: GAUSSIAN 03 (or GAUSSIAN 98 or GAUSSIAN 94) is a licensed code available from Gaussian Inc. For further information see
<http://www.gaussian.com>
- GAUSSRATE: The GAUSSRATE code is a licensed code available from the University of Minnesota. Currently the license fee is waived for all users. For further information see:
<http://comp.chem.umn.edu/gaussrate>
- *system*: This utility code is also required. (On Cray C90 the equivalent utility code is called *ishell*.) It is available in standard FORTRAN libraries with the following absolute path names:

| Machine: | File: |
|----------------------|--------------------|
| IBM RS/6000 | /usr/lib/libxlf.a |
| IRIS-Power Challenge | /usr/lib/libftn.so |

The prospective user of GAUSSRATE must obtain and install POLYRATE and GAUSSIAN 03 (or 98 or 94) before proceeding with GAUSSRATE.

The GAUSSRATE program is distributed as a compressed tar file named either `gaussrate9.1.tar.Z` or `gaussrate9.1.tar.gz`. The distributed file (either one of the above files) should be uncompressed and untarred in the `polyrate9.1` directory.

To uncompress, enter:

```
uncompress gaussrate9.1.tar.Z
```

or

```
gunzip gaussrate9.1.tar.gz
```

The uncompressed file will be named `gaussrate9.1.tar`. After extracting the files from the tar file, which can be done with the command:

```
tar -xvf gaussrate9.1.tar
```

a new directory, `gaussrate`, is created. This directory contains all the files included in the distribution package. If these instructions are followed correctly, the directory structure should be the following tree structure:

```

                                polyrate9.1
                                |
-----
|   |   |   |   |   |   |   |   |   |
doc exe gaussrate obj poten script src testo testrun util
    |
    -----
    |   |   |   |   |
    doc script source testo          testrun
                        |
                        -----
                        |   |   |   |   |
                        g03 g94 g98 ch4oh ch5 oh3 nh3oh
```

The files will be distributed among the directories as follows:

`gaussrate`: the C shell script `shuttle` and five subdirectories:

`doc`: 2 files: `gaussrate.doc` and `gaussrate.pdf`. These files are the Word and PDF versions of the GAUSSRATE manual.

`script`: 5 files containing compilation scripts for GAUSSRATE: `gaussrate.ibm`, `gaussrate.ibm604`, `gaussrate.linux`, `gaussrate.sgi`, and `gaussrate.sun`

source: 4 files comprising the source code for GAUSSRATE: `gaussrate.inc`,
`head_gr.f`, `hooks_gr.f`, and `hooks_gr.wrk`

testo: This directory contains the following subdirectories:

- g03: 12 files: `ch4ohtr1.fu6`, `ch4ohtr2.fu6`, `ch4ohtr3.fu15`,
`ch4ohtr4.fu15`, `ch4ohtr5.fu15`, `ch4ohtr6.fu15`,
`ch5tr1.fu15`, `ch5tr2.fu15`, `oh3tr1.fu15`,
`oh3tr2.fu15`, `oh3tr3.fu15`, `nh3ohtr1.fu15`
- g94: 12 files: `ch4ohtr1.fu6`, `ch4ohtr2.fu6`, `ch4ohtr3.fu15`,
`ch4ohtr4.fu15`, `ch4ohtr5.fu15`, `ch4ohtr6.fu15`,
`ch5tr1.fu15`, `ch5tr2.fu15`, `oh3tr1.fu15`,
`oh3tr2.fu15`, `oh3tr3.fu15`, `nh3ohtr1.fu15`
- g98: 12 files: `ch4ohtr1.fu6`, `ch4ohtr2.fu6`, `ch4ohtr3.fu15`,
`ch4ohtr4.fu15`, `ch4ohtr5.fu15`, `ch4ohtr6.fu15`,
`ch5tr1.fu15`, `ch5tr2.fu15`, `oh3tr1.fu15`,
`oh3tr2.fu15`, `oh3tr3.fu15`, `nh3ohtr1.fu15`

These subdirectories contain selected output files of the test runs.

testrun: 4 files: `check03`, `check94`, `check98`, and `run_all.jc`, and 4
subdirectories: `ch4oh`, `ch5`, `oh3`, and `nh3oh` with the input files for the
test calculations.

5. INSTALLATION

First the user should obtain licensed copies and install the POLYRATE and GAUSSIAN 03 (or 98 or 94) packages. Next the user should obtain a licensed copy of the GAUSSRATE package. After downloading, uncompressing, and untarring the file, the GAUSSRATE package should appear as a directory, as described in Section 4.

There are a few variables that have to be set large enough to accommodate the system or systems to be studied. These variables are set in the include file `param.inc` in the POLYRATE side of the interface. The user should consult the POLYRATE manual for additional details.

The installation of the GAUSSRATE program is carried out by running a C shell script, in particular, `gaussrate.ibm` for IBM RS/6000 computers, `gaussrate.ibm604` for IBM computers with 604e processors or Power3 processors, `gaussrate.linux` for computers using Linux operating system, `gaussrate.sgi` for Silicon Graphics IRIS-Power Challenge R10000 computers or SGI Origin 2000 R12000 computers, or `gaussrate.sun` for Sun workstations. The proper script will create a temporary directory for compilation, called `wrk`, in the `gaussrate` directory, will copy the appropriate machine-dependent file, `hooks_gr.wks`, to the `hooks_mdep.f` file, will compile the POLYRATE 9.1 files substituting the `hooks.f` file of standard POLYRATE by `hooks_gr.f` and `hooks_mdep.f`, and will create the executable file `gaussrate.exe` in the `exe` subdirectory in the `polyrate9.1` directory. The executable `gaussrate.exe` will then be accessible for all the GAUSSRATE calculations.

When executing one of these scripts, the user should also supply the number of the `param.inc` file to be used in the GAUSSRATE calculation (see Section 15.A.2 of the POLYRATE 9.1 manual for a definition of the `param.inc` file). For example, for compiling and linking GAUSSRATE using the `param.inc` file number 4, the command should be

```
gaussrate.ibm 4
```

on an IBM RS/6000 machine,

```
gaussrate.ibm604 4
```

on an IBM SP machine,

```
gaussrate.linux 4
```

on a machine running Linux,

```
gaussrate.sgi 4
```

on an SGI machine, or

```
gaussrate.sun 4
```

on an Sun machine.

In Section 9 we list the computers and operating systems on which the code has been tested. The installation of GAUSSRATE on a different kind of computer or operating system might be straightforward, requiring only changes in the compiler and loader options in any one of the scripts, `gaussrate.ibm`, `gaussrate.ibm604`, `gaussrate.linux`, `gaussrate.sgi`, or `gaussrate.sun`.

Before running GAUSSRATE, one line of the C shell script `shuttle` should be changed as described in Section 1., in order to set the *gausspath* variable to the appropriate path where GAUSSIAN 03 (or 98 or 94) is located

6. PROGRAM DESCRIPTION

The GAUSSRATE program follows the POLYRATE hooks protocol. This means that if energy, gradient, and/or Hessian calculations are desired by POLYRATE, the program calls the appropriate hooks subroutine that will return that information. (The user may read more about hooks in the POLYRATE manual.)

6.1. Description of GAUSSRATE subprograms

This is a brief description of GAUSSRATE subprograms. In most of the cases, a more detailed description is given in the comment cards at the beginning of the FORTRAN code for each subprogram.

| | |
|-----------------|--|
| <i>ehook</i> | Equivalent to the <i>ehook</i> subroutine in the POLYRATE hooks. For a given set of coordinates, it calculates the energy using GAUSSIAN 03 (or 98 or 94). |
| <i>enatin</i> | Calculates the energy for atomic systems. |
| <i>escener</i> | Carries out GAUSSIAN energy calculations. |
| <i>escfirst</i> | Carries out gaussian energy and first derivative calculations. |
| <i>escsec</i> | Carries out GAUSSIAN Hessian calculations. |
| <i>geoin</i> | Carries out GAUSSIAN geometry optimizations. |
| <i>ghook</i> | Equivalent to the <i>ghook</i> subroutine in the polyrate hooks. For a given geometry, calculates the energy and first derivatives. |
| <i>ginpene</i> | Creates the GAUSSIAN input file for energy calculations. |
| <i>ginpfrs</i> | Creates the GAUSSIAN input file for gradient calculations. |
| <i>ginpsec</i> | Creates the GAUSSIAN input file for Hessian calculations. |

| | |
|-----------------|--|
| <i>goutsec</i> | Reads the formatted checkpoint file <code>Test.FChk</code> generated by GAUSSIAN and extracts the geometry, energy, and first and second derivatives of the energy with respect to atomic coordinates. |
| <i>grest</i> | Reads and writes the information in the restart files of a GAUSSRATE restart calculation. |
| <i>headr</i> | Prints out the program header. |
| <i>hhook</i> | Equivalent to the <i>hhook</i> subroutine in the POLYRATE hooks. For a given geometry, calculates the Hessian matrix using whether GAUSSIAN or POLYRATE methods. |
| <i>ohook</i> | Equivalent to the <i>ohook</i> subroutine in the POLYRATE hooks. Optimizes a given initial geometry, using either POLYRATE or GAUSSIAN methods. |
| <i>prep</i> | Prepares the calculation and, depending on the selected options, carries out certain geometry optimizations and Hessian calculations. |
| <i>prepj</i> | Initialize variables dependent on each stationary point. |
| <i>rchmul</i> | Reads the charge and multiplicity of a system from the GAUSSIAN formatted checkpoint file. |
| <i>rcodgr</i> | Reads the input option for the GAUSSIAN runs from file <code>esp.fu70</code> . |
| <i>redinf</i> | Reads the information about reactants, products and saddle point calculated in the <i>prep</i> subroutine. |
| <i>renerg</i> | Reads the input options for GAUSSIAN energy calculations. |
| <i>rfirstgr</i> | Reads the input options for GAUSSIAN gradient calculations. |
| <i>rgenbas</i> | Reads the basis set for GAUSSIAN calculations when a nonstandard basis set is used. |

| | |
|----------------|--|
| <i>rgengr</i> | Reads the options in the general section of the <code>esp.fu70</code> input file. |
| <i>rinpgr</i> | Reads the <code>esp.fu70</code> GAUSSRATE input file. |
| <i>rlincer</i> | Reads the <i>Link0</i> options for GAUSSIAN calculations. |
| <i>rlingr</i> | Utility program for reading in a line of the <code>esp.fu70</code> input file and parsing off comments and extra spaces. |
| <i>rsecgr</i> | Reads the input options for GAUSSIAN Hessian calculations. |
| <i>rstatgr</i> | Reads the input options given in the <code>esp.fu70</code> input file for the stationary points. |
| <i>secin</i> | Carries out GAUSSIAN Hessian calculations for stationary points. |
| <i>setup</i> | Initializes some variables and calls the subroutines for reading in the <code>esp.fu70</code> input file. |
| <i>store</i> | Stores some information that could be useful in future calculations in order to avoid duplicate GAUSSIAN calls. |

Note that GAUSSRATE does not use any of the utility routines (routines starting with *y*) of the generic hooks package of POLYRATE.

6.2. Restarting a calculation

The GAUSSRATE restart option should not be confused with the POLYRATE restart options (see Section 7.C of the POLYRATE manual). The POLYRATE restart options can be used with GAUSSRATE, but GAUSSRATE also has its own, unique restart capability. The rest of this section concerns this GAUSSRATE restart capability.

The GAUSSRATE restart option is controlled by the GRRESTART keyword in the GRGENERAL section of the unit `esp.fu70` input file. The GAUSSRATE restart option is designed to take advantage of any previous calculations that may have been made on the same system, so that the number of GAUSSIAN 03 (or 98 or 94) calls is minimized. As long as the information on the stationary points from previous calculations is still applicable, a restart calculation can be made (if there is a change in any stationary point input or option, the program will not read this information, and the results of trying a restart calculation are unpredictable). This restart option allows the user to change any parameter related to the reaction path calculations using as much information as possible from previous calculations.

Two restart files are used in this kind of restart calculation: `esp.fu83`, which stores the information to be read, as originated in a previous GAUSSRATE calculation, and `esp.fu84`, where the useful information read from `esp.fu83` is stored along with the information calculated for the first time in the present GAUSSRATE run (`esp.fu84` is the file to be used for future restart runs). The `esp.fu84` file has to be created by GAUSSRATE, so if the program finds that this file exists, it will stop, to prevent overwriting a restart file.

One important practical point related to this restart option is that, if one finds that the range of the reaction path calculated in a GAUSSRATE run is not large enough to describe some effect (for example, tunneling), one can extend the calculated reaction path without repeating the calculation of the points included in the previous GAUSSRATE run. One should rename the `esp.fu84` file provided by the first run as `esp.fu83` and then run again with GRRESTART on. In a similar way, if one finds problems in the SCF convergence at some points along the reaction path, one can repeat the calculation including some of the options for improving SCF convergence available in GAUSSIAN 03 (or 98 or 94) without recalculating the well converged points. Another possibility is computing one side of the reaction path with one computer (or one processor of a

multiprocessor computer) and the other side with a different computer (or different processor); a new restart file combining the information from both calculations can be constructed by just appending one restart file to the end of the other restart file, allowing a calculation using the whole reaction path with no duplication of effort, at least in principle; in practice, due to the different precision of two different machines and round-off errors, some recalculation might be needed. One should be aware, though, that if a calculation is made using a step-size that is too large, giving a non-converged reaction path, a restart calculation using a different step-size would probably be unsuccessful, since the points along the two reaction paths would be different.

There is only one parameter related to the path that should not be changed between an original calculation and a restart calculation, namely the value of SCALEMASS. Changing this parameter will cause a miscalculation of the frequencies. It is important to note that its default value is 1.0 amu, and this is the value assumed if no reaction path calculation is desired. Therefore, if a restart calculation including the reaction path is based on a restart file written by a TST-only calculation, SCALEMASS must be set to 1 amu in order to get the right frequencies. In general, we recommend always using a value of 1.0 amu for SCALEMASS in GAUSSRATE.

A GAUSSRATE restart run requires that all the information about all the stationary points be present on file `esp.fu83`, and this data cannot be updated in this kind of restart run. However, the use of the STATUS keyword in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections of the POLYRATE `fu5` input file can alleviate this inconvenience. Thus, the user can calculate reactants and products separately and include the information obtained in the `fu5` input file. See the `ch4oh` test runs in the GAUSSRATE and Sections 7.C and 11.A of the POLYRATE manual.

The restart option works in the following way: when POLYRATE needs an energy, gradient, and/or Hessian for a given geometry, it first check if the geometry is stored in `esp.fu83`, and then it checks if the required information is stored in this same file. If one of this conditions is not fulfilled, a GAUSSIAN calculation is run to obtain the desired information. If both conditions are fulfilled, the information is read from `esp.fu83`, and no GAUSSIAN job is spawned. The geometry check is performed by comparing each of the Cartesian coordinates of the desired geometry with the Cartesian coordinates in `esp.fu83`. If the values differ by more than a criterium given by RSTTOL, the geometries are considered to be different. It is important to have an appropriate value for

RSTTOL: if the criterium is too tight, the check might fail due to the numerical round-off and to the fact that the precision of the written information is limited, and redundant calculations could be carried out, increasing unnecessarily the cpu time of the calculation. However, if this criterium is too loose, the check could be passed for two geometries that are only slightly different, and the restart option can be giving to GAUSSRATE inaccurate information. The later case can be especially true when performing reaction-path calculations with very small step-sizes, numerical differentiations, or accurate geometry optimizations. Therefore, the user must be very careful about changing this parameter. The default value is $1.D-8$, which is somehow very conservative, but it is safe. For very expensive calculations, one might want to use a higher value, but a too high value can give unphysical results. If the user increases this parameter, he or she has to be very aware of the risk it poses in the calculation, and all the results must be carefully checked. Therefore, only experienced users are advised to change this parameter.

7. DESCRIPTION OF INPUT FILES

We will assume that the user knows how to use POLYRATE 9.1 and GAUSSIAN 03 (or 98 or 94) and is familiar with all their keywords. Therefore, when talking about the common input files, we will only discuss the differences between running POLYRATE 9.1 and running GAUSSRATE 9.1

7.1. File usage

In addition to the POLYRATE 9.1 and GAUSSIAN 03 (or 98 or 94) input files, GAUSSRATE uses several files of its own for input data, for storing restart information, and for output. All these files have the name `esp.fu#`, where # denotes an integer.

| | |
|-----------------------|--|
| <code>esp.fu70</code> | General GAUSSRATE input data. |
| <code>esp.fu71</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of reactant 1, if such optimization is going to be carried out. |
| <code>esp.fu72</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of reactant 2, if the reaction studied is bimolecular and if such optimization is going to be carried out by means of the GAUSSIAN 03 (or 98 or 94) program. |
| <code>esp.fu73</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of product 1, if such optimization is going to be carried out. |
| <code>esp.fu74</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of product 2, if the reaction studied has two products and if such optimization is going to be carried out by means of the GAUSSIAN 03 (or 98 or 94) program. |
| <code>esp.fu75</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of the saddle point or constrained optimization of a reaction path starting geometry, if such optimization is desired. |
| <code>esp.fu76</code> | reserved |

| | |
|-----------------------|---|
| <code>esp.fu77</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of a well on the reactant side of the reaction path, if it exists and its optimization is going to be carried out by means of the methods in GAUSSIAN 03 (or 98 or 94). |
| <code>esp.fu78</code> | GAUSSIAN 03 (or 98 or 94) input file for geometry optimization of a well on the product side of the reaction path, if it exists and its optimization is going to be carried out by means of the methods in GAUSSIAN 03 (or 98 or 94). |
| <code>esp.fu81</code> | GAUSSIAN 03 (or 98 or 94) temporary input file, generated by GAUSSRATE. |
| <code>esp.fu82</code> | GAUSSIAN 03 (or 98 or 94) temporary output file, generated by GAUSSIAN. If the GAUSSIAN 03 (or 98 or 94) calculation fails, it can be examined in order to find out why the failure occurred. |
| <code>esp.fu83</code> | Restart file to be read during a restart calculation (see Section 6.1). |
| <code>esp.fu84</code> | Restart file to be written during a restart calculation (see Section 6.1). |
| <code>esp.fu85</code> | GAUSSRATE uses the formatted checkpoint file generated by GAUSSIAN 03 (or 98 or 94). GAUSSIAN 03 (or 98 or 94) calls this file <code>Test.FChk</code> , and GAUSSRATE does not delete it. GAUSSRATE reads this file from FORTRAN unit 85. This file will not be removed after finishing a calculation, so if the GAUSSIAN 03 (or 98 or 94) calculation fails, it can be examined in order to find the cause of the failure. |

Note that this file usage is consistent with Section 17 of the POLYRATE manual. Note also that `esp` stands for electronic structure package, and `fu` stands for FORTRAN unit. Finally note that `esp.fu76` is reserved for future use, but it is not used in this version.

7.2. Description of fu5 unit

A GAUSSRATE calculation requires some input from input units for POLYRATE. At the very least, an fu5 input file is required for indicating several options such as electronic degeneracies, temperatures for the rate constant calculations, etc. Therefore, an fu5 file must be written, exactly as if we were using an analytical potential energy surface. If the calculation requires some additional input files, the user must provide them, following the instructions in the POLYRATE 9.1 manual. It is important to clarify some points about preparing the input file for unit fu5:

RESTART

If a POLYRATE 9.1 restart run is selected (option *readful* or *readful&2* for the RESTART keyword in the GENERAL section), the program will not modify any characteristic of the calculated reaction path. We therefore advise the user to use only the restart option in GAUSSRATE, controlled by the GRRESTART keyword in GRGENERAL section of the *esp.fu70* input file, until the reaction path calculation is completely converged and all the desired tunneling options are calculated. When no more electronic structure calculations are required, the POLYRATE restart is recommended, since it is faster than the GAUSSRATE restart.

ATOMS

The ordering in the ATOMS keyword list of the GENERAL section of the input file for unit fu5 must be consistent with the ordering in unit fu75, if this unit is used in the calculation.

NOSUPERMOL

Because of the way the interface is constructed, the NOSUPERMOL keyword is required (note that SUPERMOL is the default option). Therefore, only size-consistent methods should be used in GAUSSRATE.

EZERO

Because of the way the interface is constructed, the user must choose the *calculate* option for the EZERO keyword of the ENERGETICS section, which is the default option.

POTENTIAL

The *hooks* option is required.

OPTTS and OPTMIN

In GAUSSRATE there are two ways to optimize the geometries: by means of GAUSSIAN 03 (or 98 or 94) methods or by means of POLYRATE 9.1 methods. The choice between the two methods is done in the OPTIMIZATION section of the `fu5` input file. Choosing the option *BFGS*, *NR*, or *EF*, for the OPTMIN or OPTTS keywords in the OPTIMIZATION section, will cause GAUSSRATE to use the methods native to POLYRATE 9.1, using as starting geometries those in the `fu5` input file and controlling the optimization procedure by means of the keywords selected in the OPTIMIZATION section of the `fu5` input file. In these cases, the input files `fu71` through `fu75` will not be required. The INITGEO keyword needs to take the option *GEOM* in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections of the `fu5` input file.

If the option *OHOOK* is chosen for both the OPTTS and OPTMIN keywords in the OPTIMIZATION section of the `fu5` input file, GAUSSRATE will optimize the geometries of the stationary points using the GAUSSIAN 03 (or 98 or 94) program according to the options selected in the `fu70` input file and the `fu71-fu78` input files. The initial geometries for the optimization will be those indicated in the `fu71-fu78` input files and the options selected in the OPTIMIZATION section in the `fu5` input file will be ignored. INITGEO should take the value *HOOKS* in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections of the `fu5` input file.

If the user wishes to optimize the stationary points, we recommend the use of GAUSSIAN 03 (or 98 or 94) methods; in particular this is accomplished by using the *OHOOK* option for both the OPTMIN and the OPTTS keyword in the OPTIMIZATION section of the `fu5` input file, using initial geometries given in the `fu71` through `fu75` input files, and

setting INITGEO equal to *HOOKE*. A further explanation of these keywords will be provided below.

SECOND

The calculation of the Hessian matrices can be done by numerical differentiation of the gradients, by means of the POLYRATE 9.1 methods, or by the GAUSSIAN 03 (or 98 or 94) methods, with the latter option strongly recommended. The choice is made by means of the *GHOOK* or *HHOOK* options in the HESSCAL keyword in the SECOND section of the `fu5` input file. If *HHOOK* is selected, the remaining keywords of the SECOND section are ignored and the Hessian calculations will be controlled by the options selected in the `fu70` input file. If *GHOOK* is selected, the Hessian calculation will be carried out following the options indicated in the SECOND section, ignoring the options for the Hessian calculation selected in the `fu70` input file.

Although GAUSSIAN 03 (or 98 or 94) can perform Hessian calculations using any of the electronic structure methods available in GAUSSIAN, the option of performing the Hessian calculation using POLYRATE methods is implemented for completeness. However the user is advised for efficiency reasons against using POLYRATE for the Hessian calculations.

GEOM

The ordering of the atoms in the GEOM keyword in sections REACT1, REACT2, PROD1, PROD2, and START must be consistent with the ordering in units `fu71`, `fu72`, `fu73`, `fu74`, and `fu75`, when they are used; and also the ordering in `fu75` must be consistent with the one in ATOMS in the GENERAL section.

CONSTANT

If the user selects GAUSSIAN 03 (or 98 or 94) for optimizing the geometries (this is accomplishing with the *OHOOK* option for the OPTMIN and OPTTS keywords in the OPTIMIZATION section of the POLYRATE `fu5` input), the CONSTANT keyword in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP and START sections of the `fu5` input file is meaningless. The frozen parameters must be indicated in units `fu71`-`fu78`, according to the instructions explained in the GAUSSIAN 03 (or 98 or 94) manual. If

a user selects POLYRATE 9.1 for optimizing the geometries, this keyword has the same function as in any other POLYRATE calculation, fixing the value of the selected coordinates and avoiding their optimization, as explained in Section 11.A.6 of the POLYRATE 9.1 manual.

INITGEO and STATUS

There are two options for reading the initial geometries of reactants, products, wells, and saddle point: the first one is by means of units fu71 through fu78, if a GAUSSIAN 03 (or 98 or 94) optimization is desired (*OHOOKS* option for the OPTMIN and OPTTS keywords in the OPTIMIZATION section). In this case, the INITGEO keyword has to be set to *HOOKEs*, and the files fu71-fu78 should be the appropriate input files for a GAUSSIAN 03 (or 98 or 94) optimization. The second one is by means of the GEOM keyword, if a POLYRATE 9.1 optimization (*BFGS*, *NR*, or *EF* options in the OPTMIN or OPTTS keyword in the OPTIMIZATION section) or no optimization is going to be carried out. Then, the INITGEO keyword needs to be set to *GEOM*. Therefore, the initial geometry for the optimization of those systems that are going to be optimized using GAUSSIAN 03 (or 98 or 94) methods should be given in units fu71-fu78 and the INITGEO keyword in the respective section has to be set to *HOOKEs*, while the initial geometry for those systems which are to be set to *HOOKEs*, while the initial geometry for those systems which are going to be optimized using POLYRATE methods or the optimized geometry of the systems which are not going to be further optimized should be given in unit fu5 and the INITGEO keyword in the respective sections has to be set to *GEOM*.

The combination of the keywords INITGEO, STATUS and OPTTS and OPTMIN, therefore, will indicate the procedure of the initial and/or optimized geometries for the stationary points. The combinations are:

- For optimizing the geometries using the methods in GAUSSIAN: OPTTS and OPTMIN in the OPTIMIZATION section have to be set to *OHOOKEs*, INITGEO has to be set to *HOOKEs* and STATUS set to 0 in the corresponding REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and/or START sections. The initial geometry should be given in the files fu71 through fu78.
- If the geometry optimization of one of the stationary points is not desired, the INITGEO keyword has to be set to *GEOM*, and the STATUS keyword should be set to

an allowed value greater than zero in the corresponding REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections of the `fu5` input file. The optimized geometry will be read from the `fu5` input file.

- For optimizing the geometries using the methods in POLYRATE (not recommended): OPTTS and OPTMIN in the OPTIMIZATION section have to be set to *BFGS*, *NR* and/or *EF*, and INITGEO has to be set to *GEOM* and STATUS set to 0 in the corresponding REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and/or START sections of the `fu5` input file. The initial geometry will be given in the appropriate section of the `fu5` input file. If the geometry of one of the stationary points is already optimized, the only parameter that has to be changed is the value of the STATUS keyword in the corresponding section of the `fu5` input file.

A value greater than 0 for the STATUS keyword in any of the REACT1, REACT2, PROD1, PROD2 and/or START sections involves no optimization of the geometry input in the `fu5` file and, if a value greater than 2 is selected, no Hessian calculation. If STATUS is set to 4 in the START section of the `fu5` input file, the Hessian matrix as it appears in a GAUSSIAN 03 (or 98 or 94) formatted checkpoint file can be input, according to the instructions in the POLYRATE manual.

ANHARMONICITY

Although anharmonic calculations can be carried out, the user must keep in mind the extremely high cost of numerical third or fourth derivatives of the energy when using ab initio methods. With the anharmonicity options available in POLYRATE 9.1, this extra cost is not usually warranted. We therefore recommend not using anharmonic options in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections when they require derivatives of order higher than two, at least until some later version of POLYRATE with better anharmonicity options becomes available. The only anharmonicity option that do not require derivatives higher than second are Morse I and hindered rotator.

In addition, when calculating second or higher order derivatives using the numerical methods of POLYRATE 9.1, GAUSSIAN 03 (or 98 or 94) is unable to successfully calculate some slightly distorted structures of linear molecules, such as the hydrogen molecule,

stopping in the SYMM subroutine. Therefore, we recommend that Hessians be calculated with GAUSSIAN rather than with the methods native to POLYRATE.

SCALEMASS

If restart calculations are desired, the value of the SCALEMASS variable keyword must be the same for the whole series of calculations. Note that SCALEMASS is the reduced mass to which all isoinertial coordinates are scaled. See also the discussion of SCALEMASS in Section 6.2.

7.3. Description of `esp.fu71` through `esp.fu78` input files

The data files `esp.fu71` through `esp.fu78` are GAUSSIAN-type data files. They are used only as input files for GAUSSIAN optimization on reactants 1 and 2 (`esp.fu71` and `esp.fu72`, respectively), products 1 and 2 (`esp.fu73` and `esp.fu74`), of the well on the reactant side (`esp.fu77`), of the well on the product side (`esp.fu78`), and of the saddle point or other starting geometry (`esp.fu75`). If no optimization using GAUSSIAN is desired, these files are not needed.

For constructing these files, the user must check the GAUSSIAN manual. With only one restriction, any option available for GAUSSIAN can be used; the restriction is that GAUSSIAN must generate a formatted checkpoint file at the end of the optimization. The GAUSSIAN keyword `FCHK` (or any of its equivalent keywords, `FORMCHECK` or `FCHECK`) must therefore be specified, and options in GAUSSIAN that do not generate such a file (for example, a non-standard route) cannot be used.

As mentioned above, when creating these files, the order of the atoms in unit `fu75` must be consistent with the order of the atoms input in the `ATOMS` keyword in the `GENERAL` section of the `POLYRATE fu5` input file, and the order of the atoms in units `fu71-fu78` must be consistent with the index specifications in the `GEOM` keyword in the `REACT1`, `REACT2`, `PROD1`, `PROD2`, `WELLR`, `WELLP`, and `START` sections of the `fu5` input file.

For the sake of consistency, the method chosen for the electronic structure calculations for a given reaction must be the same in all the `esp.fu71` through `esp.fu78` files representing the species for that reaction. Only if one of the species is the hydrogen atom and electronic correlation is included can the quantum methods be different (since no correlation energy can be calculated for the hydrogen atom). The electronic structure method must also be consistent with the options related to energy and first and second derivatives chosen in the `fu70` input file.

When studying a reaction with no saddle point, the user must insure that the optimization procedures chosen for the starting point will not lead the system to reactants or products. This can be accomplished by freezing the appropriate geometrical parameters. If no geometrical parameter is kept fixed, the optimization will lead to a point where the

gradients are zero and the procedure for following the reaction path will not work successfully.

7.4. Description of `esp.fu70` input file

Along with the input `fu5` file, which controls the POLYRATE options, the `fu70` input file will control all of the GAUSSRATE options and some of the GAUSSIAN input options. The `fu70` input file is divided into sections which, like the `fu5` sections, are denoted by a header preceded by an asterisk (*). There are eight sections, each starting with GR in order to avoid confusion with similar sections in the `fu5` input file. These sections are GRGENERAL, GRCOMMON, GRREACT1, GRREACT2, GRPROD1, GRPROD2, GRWELLR, GRWELLP, GRSTART and GRPATH. In these sections, the appropriate keywords have to be specified.

| Section name | Description |
|--------------|---|
| GRGENERAL | Restart options |
| GRCOMMON | GAUSSIAN options common to all the stationary points |
| GRREACT1 | GAUSSIAN options specific to the first reactant |
| GRREACT2 | GAUSSIAN options specific to the second reactant, if any |
| GRPROD1 | GAUSSIAN options specific to the first product |
| GRPROD2 | GAUSSIAN options specific to the second product, if any |
| GRWELLR | GAUSSIAN options specific to the reactant well, if any |
| GRWELLP | GAUSSIAN options specific to the product well, if any |
| GRSTART | GAUSSIAN options specific to the starting (or saddle) point |
| GRPATH | GAUSSIAN options common to all the nonstationary points along the reaction path |

There are three type of keywords: switch (which does not have any argument), variable (which requires one argument following the keyword), and list (which requires a list of options, with an END line). See the POLYRATE manual for a more thorough discussion of the three types of keywords.

7.4.1. The GRGENERAL section

The GRGENERAL section controls GAUSSRATE 's own options. There are only three keywords allowed in this section, GRRESTART and NOGRRESTART, with GRRESTART being the default, and RSTTOL.

GRRESTART (NOGRRESTART)

This is a switch keyword that tells the program to check the restart file `esp.fu83` and search for information about the point to be calculated. If it finds the required information about that point, the program writes it in the `esp.fu84` file and uses the stored information instead of calculating it. If the information needed is not present in the `fu83` file, GAUSSRATE runs GAUSSIAN and writes the GAUSSIAN output information to unit `fu84`. If NOGRRESTART is selected, neither reading file `fu83` nor writing file `fu84` will be performed.

RSTTOL

RSTTOL is a variable keyword that must be followed by a real number, which is the value of the tolerance in the comparison of geometries between the geometry currently used by GAUSSRATE and the geometry found in a restart file `esp.fu83`. The meaning of this keyword is explained in detail in Section 6.2. The inexperienced user is not advise to change this value from its default value, $1.E-8$.

Example:

```
RSTTOL          0.00000001
```

7.4.2. The GRCOMMON section

The GRCOMMON section reads the information common to all the GAUSSIAN calculations for the stationary points and points along the reaction path, excepting the GAUSSIAN 03 (or 98 or 94) geometry optimizations, which are totally controlled by the fu71 through fu78 input file. The options selected in this section will be applied to all the GAUSSIAN calculations unless a different keyword is specified in the section corresponding to a specific point. This section needs to precede the specific sections GRREACT1, GRREACT2, GRPROD1, GRPROD2, GRSTART, GRWELLR, GRWELLP, and GRPATH. The following keywords are allowed in the GRCOMMON section:

GRENER

This is a list type keyword and therefore it must include an END line to indicate the end of the list (see the POLYRATE manual for a description of list keywords). GRENER includes the keywords that GAUSSIAN will use for carrying out an energy calculation. The default for this keyword is *#HF/STO-3G UNITS=AU FCHK NOSYM*. In order to get the desired results, two particular keywords must always be supplied for this kind of calculation: *UNITS=AU* and *FCHK* (or their equivalent GAUSSIAN keywords; see the GAUSSIAN manual for a discussion of alternative forms of GAUSSIAN keywords). No blank lines can appear in this list, since GAUSSIAN would take those blank lines as the end of keyword inputs. Just as in GAUSSIAN inputs, the pound symbol (#) must precede the complete set of keywords.

Example:

```
GRENER
#HF/6-31G SCF=QC UNITS=AU FCHK
END
```

GRFIRST

This accomplishes a similar purpose as the GRENER keyword, but it indicates the keywords to be used in gradient calculations. Again, *UNITS=AU* and *FCHK* are required. The default is *#HF/STO-3G UNITS=AU FCHK NOSYM FORCE*.

GRSEC

This keyword is only used when the *HHOOK* option is specified in the HESSCAL keyword of the SECOND section of the fu5 input file. It accomplishes a purpose similar to the GRENER and GRFIRST keywords, but indicating the options for a Hessian calculation.

UNITS=AU and *FCHK* are required, and the *NORAMAN* option is recommended (since it saves computer time). The default is *#HF/STO-3G UNITS=AU FCHK NOSYMM
FREQ=NORAMAN*.

GRLINK0

GRLINK0 is a list keyword for indicating the link0 options for GAUSSIAN calculations (note that the last character is zero). This keyword controls the options for renaming scratch files, creating checkpoint files, determining memory size, etc. If it is not indicated, no link0 options are assumed, since they are not needed for the calculations. If indicated, they are assumed to be the same for all the GAUSSIAN calculations, no matter which species or type of calculation is involved, the only exception being the GAUSSIAN 03 (or 98 or 94) optimizations which are fully controlled by the fu70 through fu78 input files. No blank lines are allowed in this keyword.

GRBASIS

When running GAUSSIAN, if a non-standard basis set is desired, the keyword GEN must be indicated, and the general basis set must follow the geometry specification in the GAUSSIAN input. If a non-standard basis set is desired in a GAUSSRATE calculation, it must be indicated in GRBASIS, and it must be the same for all the calculations on all the systems. Again, no blank lines are allowed, and (because of dimension limitations) a maximum of 100 lines are allowed for indicating the basis set. If a larger space is required, the basis set can be specified by an external file, using the symbol '@' (see the GAUSSIAN 03 (or 98 or 94) manual for further details of this option). For example, for selecting a modified STO-3G basis set, located in the msto3g.gbs file in the directory /usr/g94/basis, one should write:

Example:

```
GRBASIS
@/usr/g94/basis/msto3g.gbs
END
```

Although the above example illustrates what will probably be the most common use for this keyword, actually any information that needs to be located in a GAUSSIAN input file after the geometry specification can be included by means of the GRBASIS keyword. For example, electronic excited states require input information indicating the orbitals involved in the electronic excitation; this information can be entered by this keyword with two limitations: the information will be included in all the GAUSSIAN inputs (except the optimizations, which are read directly from units `fu71-fu78`), and no blank lines are allowed in this keyword. The later limitation can be overcome by using the external file option mentioned in the previous paragraph.

It should be noted that the isotope input, which must be contained in this section of the GAUSSIAN 03 (or 98 or 94) input file if nonstandard isotopes are desired, should never be included in a GAUSSRATE run. The choice of the isotopic masses has to be done in the `fu5` input file of POLYRATE.

7.4.3. The GRREACT1, GRREACT2, GRPROD1, GRPROD2, GRWELLR, GRWELLP, GRSTART, and GRPATH sections

Since in some cases, the options selected in the GRCOMMON section might not be the most useful for all the points to be calculated, these eight sections allow us to select different keywords for the energy, gradients, and Hessian calculations by means of the GRENER, GRFIRST, and GRSEC list keywords. The options for the first reactant should be specified in the GRREACT1 section; in the GRREACT2 the options for the second reactant, if it exists; in GRPROD1 and GRPROD2 the options for the first product and, if it exists, the second one; in GRWELLR the options for a well on the reactant side of the reaction path, if it exists; in GRWELLP the options for a well on the product side, if it exists; section GRSTART will indicate the options for the saddle point or starting geometry, and GRPATH will indicate the options for GAUSSIAN calculations on the non-stationary points along the reaction path. If no changes from the options selected in the GRCOMMON section are wanted, these sections can be skipped.

These sections can include one or more of the GRENER, GRFIRST, and GRSEC keywords explained above for the GRCOMMON section, with the same syntax that we explained in the previous section, and requiring the keywords *UNITS=AU* and *FCHK* in all the inputs.

In order to avoid problems related to the reorientation of the systems that GAUSSIAN 03 (or 98 or 94) performs, in addition to *UNITS=AU* and *FCHK*, the keyword *NOSYMM* is strongly recommended for its use in the GRPATH section; otherwise, the results could be wrong even though they would seem reasonable and no error would be detected without a careful study of the directions of the gradients (see the POLYRATE manual for a more thorough discussion of reorientation problems and GAUSSIAN reorientation).

The *NOSYMM* keyword is also recommended when third or fourth derivatives of the energy are needed (i.e., for anharmonic calculations or when using the cubic algorithm for starting the reaction path) and when the *GHOOK* option is selected for the HESSCAL keyword in the SECOND section of the *fu5* input file is on, since for the numerical differentiation of the derivatives computed using GAUSSIAN it is necessary to have them oriented in a consistent way.

The options entered by means of GRBASIS and GRLINK0 keywords in the GRCOMMON section are used in all the GAUSSIAN calculations for which input is constructed by GAUSSRATE (all the calculations but geometry optimizations, for which the input is written by the user in units $f_{u71}-f_{u78}$); therefore, the GRBASIS and GRLINK0 keywords are only allowed in the GRCOMMON section and not in the .GRREACT1, GRREACT2, GRPROD1, GRPROD2, GRWELLR, GRWELLP, GRSTART, and GRPATH sections.

Besides using the GRENER, GRFIRST, and GRSEC keywords, some additional issues need to be clarified, and two new keywords need to be introduced:

CHARGE and MULTIPLICITY

If GAUSSIAN optimization is required, GAUSSRATE will read the charge and multiplicity of each species from the GAUSSIAN optimization output. Nevertheless, if no optimization is selected or if POLYRATE 9.1 is selected for carrying out the optimizations, GAUSSRATE will need to know the charge and multiplicity of the system before making any GAUSSIAN calculation. The way to input these characteristics is by means of the CHARGE and MULTIPLICITY keywords. These keywords are not allowed in the GRCOMMON section since they are dependent on the species and are only required for the systems which will not be optimized using GAUSSIAN 03 (or 98 or 94), being ignored if they are specified for a species that is going to be optimized using GAUSSIAN. For the points along the reaction path, the charge and multiplicity are assumed to be the same as the values for the saddle point or starting geometry, and if they are specified in the GRPATH section they will also be ignored.

CHARGE is a variable keyword that must be followed by an integer, which is the value of the charge of the system. The default value for CHARGE is 0. MULTIPLICITY is also a variable keyword followed by an integer indicating the multiplicity of the species. The default value for MULTIPLICITY is 1, which corresponds to a singlet. Values of 2 and 3 correspond to doublets and triplets.

Example:

| | |
|--------------|----|
| CHARGE | -1 |
| MULTIPLICITY | 2 |

8. TESTING GAUSSRATE

8.1. Tests performed

We tested the version 9.1 of GAUSSRATE using version 9.1 of POLYRATE and the indicated versions of GAUSSIAN 03/98/94 on the following machines (the operating system is indicated in parentheses):

1. IBM SP with Power3 processor (AIX 4.3.4.0); GAUSSIAN 98 Rev. A.11; GAUSSIAN 03 Rev. B.01
2. SGI Origin 2000 R12000 (IRIX 6.5.12f); GAUSSIAN 94 Rev. E.2; GAUSSIAN 98 Rev. A.11; GAUSSIAN 03 Rev. B.01
3. Netfinity Linux Cluster (RedHat Linux 7.2); GAUSSIAN 98 Rev. A.11.3; GAUSSIAN 03 Rev. B.01
4. Sun Blade 2000 R12000 (Solaris 8); GAUSSIAN 98 Rev. A.11; GAUSSIAN 03 Rev. B.01

The code is expected to work with all GAUSSIAN 03/98/94 versions that use input files and formatted checkpoint files with the same structure as the above mentioned versions.

8.2. Test suite

The purpose of the test suite is to provide some examples of the way GAUSSRATE works, not to check all GAUSSIAN 03 (or 98 or 94) or POLYRATE 9.1 options. Therefore, the number of tests included is only ten, and the tests illustrate only the most basic features of GAUSSRATE. The level of calculation, size of the systems, and computational requirements of the test runs have been chosen in such a way that running the whole suite does not consume an inordinate amount of computing time. All the test runs were run after compiling GAUSSRATE using the `param4.inc` file.

The test suite is located in the `testrun` directory that contains several subdirectories. Each subdirectory contains one or more tests based on the same reaction. The summary output files for these test runs that are distributed in the current version of the program are located in the `testo` directory. (The output files were obtained in runs on a SGI Origin 2000 machine.) The Korn shell scripts `check03`, `check98`, and `check94` in the `testrun` directory allow an easy comparison between the `poly.ful5` output files obtains after running all the test runs using GAUSSIAN 03, GAUSSIAN 98, and GAUSSIAN 94, respectively, and the equivalent `poly.ful5` files in the `testo` directory.

Each directory in `testrun` includes one or more tests based on one of the following reactions:

| Reaction | Directory | Test names |
|--|--------------------|--|
| $\text{CH}_3 + \text{H}_2 \rightarrow \text{CH}_4 + \text{H}$ | <code>ch5</code> | <code>ch5tr1</code> , <code>ch5tr2</code> |
| $\text{OH} + \text{H}_2 \rightarrow \text{H}_2\text{O} + \text{H}$ | <code>oh3</code> | <code>oh3tr1</code> , <code>oh3tr2</code> , <code>oh3tr3</code> . |
| $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ | <code>ch4oh</code> | <code>ch4ohtr1</code> , <code>ch4ohtr2</code> , <code>ch4ohtr3</code> , <code>ch4ohtr4</code> , <code>ch4ohtr5</code> , <code>ch4ohtr6</code> . |
| $\text{NH}_3 + \text{OH} \rightarrow \text{NH}_2 + \text{H}_2\text{O}$ | <code>nh3oh</code> | <code>nh3ohtr1</code> |

The test runs are run in a subdirectory created for each run. This way, problems that could be caused when running other GAUSSIAN or GAUSSRATE calculations in the same directory that GAUSSRATE is using are avoided. After the test run is completed, the directory is removed and the temporary files created are moved to the `GRTEMPFILES` directory.

8.2.1. Test run `ch5tr1`

Tunneling: SCT
Number of levels: single level
Hindered rotation: none

This sample run for the reaction $\text{CH}_3 + \text{H}_2 \rightarrow \text{CH}_4 + \text{H}$ gives the same results as the test run `ch5fu30tr5` included in the POLYRATE 9.1 test suite. It performs calculations of the TST, CVT and ICVT rate constants at the UHF/STO-3G level, and it is based on following the reaction path using the Euler steepest descents method (also called Euler single-step method). For all the stationary points symmetry is employed in all the GAUSSIAN calculations (which is the default for GAUSSIAN calculations); nevertheless, this option is turned off when calculating points along the reaction coordinate in order to avoid possible problems due to the reorientation of the system. A restart file is created (GRRESTART keyword), and all the input of the geometries is done by means of files `fu71` through `fu75`, in order to allow GAUSSIAN to optimize the stationary points (*ohook* option in OPTTS and *optmin* in the OPTIMIZATION section of the `fu5` input file, and INITGEO set to *hooks* in the REACT1, REACT2, PROD1, PROD2, and START sections in the input file `fu5`).

| GAUSSRATE I/O files | GAUSSRATE file names | |
|--------------------------|------------------------|---|
| <code>ch5tr1.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch5tr1.71</code> | <code>esp.fu71</code> | Input data for reactant 1 |
| <code>ch5tr1.72</code> | <code>esp.fu72</code> | Input data for reactant 2 |
| <code>ch5tr1.73</code> | <code>esp.fu73</code> | Input data for product 1 |
| <code>ch5tr1.74</code> | <code>esp.fu74</code> | Input data for product 2 |
| <code>ch5tr1.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>ch5tr1.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch5tr1.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>ch5tr1.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>ch5tr1.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>ch5tr1.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.2. Test run `ch5tr2`

Tunneling: SCT
Number of levels: single level
Hindered rotation: none

This test run uses the restart file created by the previous run and performs a calculation using the ISPE technique by using ten MP2/6-31G** energies input in the `esp.fu51` input file. Of these ten energies, two are for products and the saddle point, and eight are for nonstationary points. Since the ISPE technique does not modify the reaction path, the calculation can be restarted successfully. The user must run the `ch5tr1` test run before running `ch5tr2`, in order to create the restart file to be read, `ch5tr2.rst`, which will be a copy of the `ch5tr1.rst` file generated by the previous run and located in the same directory.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|-----------------------------|------------------------|--|
| <code>ch5tr2.51</code> | <code>poly.fu51</code> | Input data for ISPE information |
| <code>ch5tr2.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch5tr2.71</code> | <code>esp.fu71</code> | Input data for reactant 1 |
| <code>ch5tr2.72</code> | <code>esp.fu72</code> | Input data for reactant 2 |
| <code>ch5tr2.73</code> | <code>esp.fu73</code> | Input data for product 1 |
| <code>ch5tr2.74</code> | <code>esp.fu74</code> | Input data for product 2 |
| <code>ch5tr2.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>ch5tr2.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch5tr2.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>ch5tr2.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>ch5tr2.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>ch5tr2.rst.old</code> | <code>esp.fu83</code> | Restart file read by GAUSSRATE |
| <code>ch5tr2.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.3. Test run `oh3tr1`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is a test run for a conventional TST calculation for the reaction $\text{OH} + \text{H}_2 \rightarrow \text{H}_2\text{O} + \text{H}$. The geometries for the reactants and products are given (it is assumed that they already are fully optimized) in the `fu5` input file (INITGEO is set to `geom`, and STATUS set to 2 in the REACT1, REACT2, PROD1 and PROD2 sections of the `fu5` input file), while the saddle point optimization is carried out by means of GAUSSIAN, requiring, therefore, the `esp.fu75` input file, and STATUS set to 0 and the option `hooks` for the INITGEO keyword in the START section of the input file `fu5`. The GAUSSRATE restart file `esp.fu84` is written. The level of electronic structure calculation used for this test run is MP2, using Dunning's aug-cc-pVDZ basis set, which is entered by means of the GRBASIS keyword. The unformatted checkpoint file generated for GAUSSIAN is renamed `oh3tr1.chk` by means of the GRLINK0 keyword.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|--------------------------|------------------------|--|
| <code>oh3tr1.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>oh3tr1.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>oh3tr1.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>oh3tr1.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>oh3tr1.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>oh3tr1.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>oh3tr1.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.4. Test run `oh3tr2`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is a test run that, by making use of the `oh3tr1.rst` file previously written by the `oh3tr1` test run, restarts the calculation performed by the previous test run and makes a canonical variational theory (CVT) calculation, without tunneling, by following the reaction path using the variational reaction path algorithm based on the Euler method (*VRPE* option of RPM keyword) with a step size of 0.025 bohr. The reaction path is calculated between -0.3 bohr and $+0.3$ bohr. Nonredundant internal coordinates are used for describing the vibrations. The user must run the `oh3tr1` test run before running `oh3tr2`, since the restart file to be read, `oh3tr2.rst`, will be a copy of the `oh3tr1.rst` file generated by the previous run and located in the same directory. Otherwise, the `oh3tr2.rst` file will not exist, and the program will calculate the frequencies for all the stationary points and the optimum geometry for the saddle point instead of reading them from the restart file. It should be noted that the `fu75` file is required, and it is used by GAUSSRATE although not by GAUSSIAN. At the end of the calculation, a new restart file, including the information calculated for the first time in the present run, will take the name of `oh3tr2.rst`, while the old restart file will be renamed as `oh3tr2.rst.old` (and this will be unchanged from what was in file `oh3tr1.rst` at the start of the present run).

| GAUSSRATE I/O files | GAUSSRATE file names | |
|-----------------------------|------------------------|---|
| <code>oh3tr2.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>oh3tr2.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>oh3tr2.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>oh3tr2.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>oh3tr2.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>oh3tr2.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>oh3tr2.rst.old</code> | <code>esp.fu83</code> | Restart file read by GAUSSRATE |
| <code>oh3tr2.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.5. Test run oh3tr3

Tunneling: none
Number of levels: single level
Hindered rotation: none

This test run uses the `oh3tr2.rst` file written by the `oh3tr2` test run, copying it as `oh3tr3.rst`, and it performs the same calculation as the `oh3tr1` test. Since more information than is required for the calculation is stored in the `oh3tr2.rst` file, the restart file created by this test run, `oh3tr3.rst`, will be smaller than the file `oh3tr2.rst`. This is the reason why it is convenient to keep the file from which a restart calculation reads the information (in the executable scripts of these test runs, such files are renamed with the extension `old`). No GAUSSRATE calculations are needed for this test run, so it is the fastest test run of the suite.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|-----------------------------|------------------------|--|
| <code>oh3tr3.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>oh3tr3.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>oh3tr3.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>oh3tr3.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>oh3tr3.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>oh3tr3.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>oh3tr3.rst.old</code> | <code>esp.fu83</code> | Restart file read by GAUSSRATE |
| <code>oh3tr3.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.6. Test run `ch4ohtr1`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is the first of a series of tests that try to show how GAUSSRATE would usually be used. We study the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. The sequence actually has five stages. The first four stages may be thought of a complete single-level calculation or as runs 1-4 of a five-run dual-level calculation. The first step we will take is the calculation of the first reactant, CH_4 . In the `fu5` input file we only include the REACT1 section, and only the additional input files `fu70` and `fu71` are required. The GAUSSRATE restart option is `off`, since the restart is only available when all the information about the stationary points is read from the restart file or written in it.

The output file `esp.fu61` will contain the information calculated for this reactant, and this information will be included in the `fu5` input file for the following runs. (The values included in the released version were obtained on an IBM SP machine using GAUSSIAN 03.)

| GAUSSRATE I/O files | GAUSSRATE file names | |
|---------------------------|-----------------------|---|
| <code>ch4ohtr1.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch4ohtr1.71</code> | <code>esp.fu71</code> | Input data for reactant 1 |
| <code>ch4ohtr1.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch4ohtr1.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about reactant 1 |
| <code>ch4ohtr1.fu6</code> | <code>poly.fu6</code> | Long output file |

8.2.7. Test run `ch4ohtr2`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is the second run in the four-stage single-level calculation for the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. The information included in the `fu61` output file from the previous run is cut and pasted to the `fu5` input file for the present run. The properties of the other reactant, OH, and the products, CH_3 and H_2O , are calculated here. Therefore, the `fu5` input file will not contain the START section, and the input files `fu70`, `fu72`, `fu73`, and `fu74` are required. Once again, the GAUSSRATE restart option is *off*.

Usually, the user would calculate the stationary points one by one, instead of calculating three in a row. Thus, if some problem is encountered in any stationary point calculation, the user can check the error in that particular point, instead of repeating several optimizations.

The `fu61` input file will contain all the information about the reactants and products needed for the next run. This includes both the information calculated in test run `ch4ohtr1` and the information calculated in the present test run. (The values included in the released version were obtained on an IBM SP machine using GAUSSIAN 03.)

| GAUSSRATE I/O files | GAUSSRATE file names | |
|---------------------------|-----------------------|--|
| <code>ch4ohtr2.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch4ohtr2.72</code> | <code>esp.fu72</code> | Input data for reactant 2 |
| <code>ch4ohtr2.73</code> | <code>esp.fu73</code> | Input data for product 1 |
| <code>ch4ohtr2.74</code> | <code>esp.fu74</code> | Input data for product 2 |
| <code>ch4ohtr2.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch4ohtr2.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>ch4ohtr2.fu6</code> | <code>poly.fu6</code> | Long output file |

8.2.8. Test run `ch4ohtr3`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is the third run in the four-stage single-level calculation for the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. In this test run, we calculate the saddle point properties and evaluate the conventional TST rate constant, including all the information on reactants and products in the `fu5` input file, as they appeared in the `fu61` output file from the previous run. (The values included in the released version were obtained on an IBM SP machine using GAUSSIAN 03.)

| GAUSSRATE I/O files | GAUSSRATE file names | |
|---------------------------|-----------------------|--|
| <code>ch4ohtr3.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch4ohtr3.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>ch4ohtr3.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch4ohtr3.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>ch4ohtr3.fu6</code> | <code>poly.fu6</code> | Long output file |

8.2.9. Test run `ch4ohtr4`

Tunneling: SCT
Number of levels: single level
Hindered rotation: mode 14

This is the fourth and final run in the four-stage calculation for the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. Actually this fourth stage may be considered either as stage 4 of a complete four-stage single-level calculation or as the fourth stage in five-stage dual-level calculation. In this test run we use the information about the stationary points appearing in the `fu61` output file from the `ch4ohtr3` test run and evaluate the reaction path, CVT, CVT/ZCT and CVT/SCT rate constants using Euler method.

We assumed the hindered rotor approximation for treating the lower vibrational mode along the reaction path, and we calculated the vibrational frequencies by using redundant internal coordinates.

The GAUSSRATE restart option was selected in the `fu70` input file, writing the information for future calculations in the `fu84` file. It is interesting to note that, since no GAUSSIAN calculation is carried out for the saddle point in this particular run, the charge and multiplicity for the nonstationary points along the reaction path must be provided in the START section of the `fu70` file (since the program assumes that these nonstationary points have the same charge and multiplicity as the saddle point).

The Hessians along the reaction path are calculated using the keywords (specified in GRSEC list keyword in the GRPATH section of the `fu70` input file):

```
#PM3 OPT=(NOEIGENTEST,CALCFC) UNITS=AU FCHK NOSYMM OPTCYC=1
```

The reason for using these keywords, rather than `FREQ` as in the other test runs, is that when using the `FREQ` keyword for calculating the frequencies, some calculations of points along the reaction path performed with revision B.1 of GAUSSIAN 94 stop when the program reaches the *matcor* subroutine. The keywords given above make GAUSSIAN follow a different route, avoiding the *matcor* subroutine, ending successfully, and providing GAUSSRATE with the required information.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|---------------------|----------------------|--|
| ch4ohtr4.70 | esp.fu70 | Input data for GAUSSRATE |
| ch4ohtr4.dat | poly.fu5 | Input data for POLYRATE |
| ch4ohtr4.61 | esp.fu61 | POLYRATE output file containing information about the stationary points |
| ch4ohtr4.fu6 | poly.fu6 | Long output file |
| ch4ohtr4.fu15 | poly.fu15 | Summary output file |
| ch4ohtr4.rst | esp.fu84 | Restart file written by GAUSSRATE |

8.2.10. Test run `ch4ohtr5`

Tunneling: LCT
Number of levels: dual level
Hindered rotation: mode 14

This test run completes a IOC dual-level calculation of the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. The lower-level information is read from the restart file from the previous run. The higher-level data is included by means of the `fu50` file. Tunneling is calculated by the microcanonical optimized multidimensional tunneling method (muOMT), requiring therefore some calculation in the reaction-swath region that are not present in the restart file, since the tunneling for the previous run was calculated using the SCT approach. The frequencies are calculated using Cartesian coordinates, instead of the set of redundant curvilinear coordinates from the `ch4ohtr4` run. Since the different choice of coordinates does not affect the reaction path calculation, the restart option does not prevent us from changing the coordinate system from one run to another. The hindered rotor approximation is used for computing the partition function of the lowest vibrational mode. The lowest four frequencies are interpolated directly by the IVTST-0 interpolation algorithm.

The restart file to be read is copied from the `ch4ohtr4.rst` file, generated by the previous run, `ch4ohtr4`. The user should, therefore, run the previous run (`ch4ohtr4`) in this set of tests before running this one. A new restart file, which includes all the previous information plus the additional calculations needed for estimating the LCT tunneling, is generated by this test run.

Since GAUSSRATE tries to minimize the number of calculations spooled to GAUSSIAN, any calculation involves several checking steps, which can actually slow the GAUSSRATE calculation when the GAUSSIAN jobs are as fast as in this set of test runs. This fact, added to the large requirements of input-output data transfer, make this calculation (and, in general, any calculation based on semiempirical methods) much slower when using GAUSSRATE than when using MORATE.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|---------------------|----------------------|--|
| ch4ohtr5.70 | esp.fu70 | Input data for GAUSSRATE |
| ch4ohtr4.rst | esp.fu83 | Restart file read by GAUSSRATE |
| ch4ohtr5.dat | poly.fu5 | Input data for POLYRATE |
| ch4ohtr5.50 | poly.fu50 | Additional input data for the POLYRATE VTST-IC calculation |
| ch4ohtr5.61 | esp.fu61 | POLYRATE output file containing information about the stationary points |
| ch4ohtr5.fu6 | poly.fu6 | Long output file |
| ch4ohtr5.fu15 | poly.fu15 | Summary output file |
| ch4ohtr5.rst | esp.fu84 | Restart file written by GAUSSRATE |

8.2.11. Test run `ch4ohtr6`

Tunneling: LCT
Number of levels: dual level
Hindered rotation: mode 14

This test run completes a IOC dual-level calculation of the $\text{CH}_4 + \text{OH} \rightarrow \text{CH}_3 + \text{H}_2\text{O}$ reaction. The lower-level information is read from the restart file from the `ch4ohtr4` run. The higher-level data is included by means of the `fu50` file. Tunneling is calculated by the microcanonical optimized multidimensional tunneling method (muOMT), with LCT method being calculated using the LCG4 approach. The frequencies are calculated using Cartesian coordinates, instead of the set of redundant curvilinear coordinates from the `ch4ohtr4` run. Since the different choice of coordinates does not affect the reaction path calculation, the restart option does not prevent us from changing the coordinate system from one run to another. The hindered rotor approximation is used for computing the partition function of the lowest vibrational mode. The lowest four frequencies are interpolated directly by the IVTST-0 interpolation algorithm.

The restart file to be read is copied from the `ch4ohtr4.rst` file, generated by the previous run, `ch4ohtr4`. The user should, therefore, run the previous run (`ch4ohtr4`) in this set of tests before running this one. A new restart file, which includes all the previous information plus the additional calculations needed for estimating the LCT tunneling, is generated by this test run.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|----------------------------|------------------------|---|
| <code>ch4ohtr6.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>ch4ohtr4.rst</code> | <code>esp.fu83</code> | Restart file read by GAUSSRATE |
| <code>ch4ohtr6.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>ch4ohtr6.50</code> | <code>poly.fu50</code> | Additional input data for the POLYRATE VTST-IC calculation |
| <code>ch4ohtr6.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>ch4ohtr6.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>ch4ohtr6.fu15</code> | <code>poly.fu15</code> | Summary output file |
| <code>ch4ohtr6.rst</code> | <code>esp.fu84</code> | Restart file written by GAUSSRATE |

8.2.12. Test run `nh3ohtr1`

Tunneling: none
Number of levels: single level
Hindered rotation: none

This is a test run for the $\text{NH}_3 + \text{OH} \rightarrow \text{NH}_2 + \text{H}_2\text{O}$ reaction including a well on the reactant side and a well on the product side. The geometries are optimized by means of GAUSSIAN methods. Therefore, the initial geometries and keywords for the optimization are given in the input files `esp.fu71-75`, `esp.fu77`, and `esp.fu78`, and INITGEO is set to *hooks* and STATUS to 0 in the REACT1, REACT2, PROD1, PROD2, WELLR, WELLP, and START sections of the `fu5` input file. The Hessian matrices are also calculated, as recommended, using the methods in GAUSSIAN. With the information for the stationary points obtained in this way, a conventional TST rate constant without tunneling is calculated.

| GAUSSRATE I/O files | GAUSSRATE file names | |
|----------------------------|------------------------|--|
| <code>nh3ohtr1.70</code> | <code>esp.fu70</code> | Input data for GAUSSRATE |
| <code>nh3ohtr1.71</code> | <code>esp.fu71</code> | Input data for reactant 1 |
| <code>nh3ohtr1.72</code> | <code>esp.fu72</code> | Input data for reactant 2 |
| <code>nh3ohtr1.73</code> | <code>esp.fu73</code> | Input data for product 1 |
| <code>nh3ohtr1.74</code> | <code>esp.fu74</code> | Input data for product 2 |
| <code>nh3ohtr1.75</code> | <code>esp.fu75</code> | Input data for the saddle point |
| <code>nh3ohtr1.77</code> | <code>esp.fu77</code> | Input data for the reactant well |
| <code>nh3ohtr1.78</code> | <code>esp.fu78</code> | Input data for the product well |
| <code>nh3ohtr1.dat</code> | <code>poly.fu5</code> | Input data for POLYRATE |
| <code>nh3ohtr1.61</code> | <code>esp.fu61</code> | POLYRATE output file containing information about the stationary points |
| <code>nh3ohtr1.fu6</code> | <code>poly.fu6</code> | Long output file |
| <code>nh3ohtr1.fu15</code> | <code>poly.fu15</code> | Summary output file |

8.3. Test run timings

Here are the timings for the test runs, in CPU seconds.

The following timings apply to version 8.1.1/P8.1.1-G94, with the GAUSSIAN versions listed in Section 9.

| | IBM SP/604e | SGI Origin 2000 |
|-------------------|----------------|--------------------|
| Test run ch5tr1 | 2949.9 | 36.6 |
| Test run ch5tr2 | 14.2 | 5.2 |
| Test run oh3tr1 | 1315.8 | 82.0 |
| Test run oh3tr2 | 7559.1 | 773.5 |
| Test run oh3tr3 | 0.0 | 0.0 |
| Test run ch4ohtr1 | 3.4 | 0.7 |
| Test run ch4ohtr2 | 10.1 | 14.4 |
| Test run ch4ohtr3 | 8.7 | 12.4 |
| Test run ch4ohtr4 | 3155.2 | 4073.2 |
| Test run ch4ohtr5 | 944.1 | 917.7 |
| Test run nh3ohtr1 | 42.0 | 54.5 |

9. COMPUTERS, OPERATING SYSTEMS, AND GAUSSIAN VERSIONS ON WHICH THE CODE HAS BEEN DEVELOPED AND TESTED

In each case we give the GAUSSRATE version number, then the computers and operating system on which GAUSSRATE was tested. For each computer and operating system we also specify the GAUSSIAN version that was used for testing.

| GAUSSRATE Version | Machine (Operating system) | GAUSSIAN Version | | |
|---------------------------------|--|------------------|----|----|
| | | 94 | 98 | 03 |
| 7.1/P7.1.1-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.1) | B.1 | | |
| | Cray C90 (UNICOS 8.0.3) | D.3 | | |
| | Silicon Graphics IRIS-Power Challenge L R8000 (IRIX 6.2) | B.1 | | |
| 7.2/P7.2-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.1) | B.1 | | |
| | Cray C90 (UNICOS 8.0.3) | D.3 | | |
| | Silicon Graphics IRIS-Power Challenge L R8000 (IRIX 6.2) | B.1 | | |
| 7.3/P7.3-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.2) | B.1 | | |
| | Cray C90 (UNICOS 8.0.3) | D.4 | | |
| | Silicon Graphics IRIS-Power Challenge L R8000 (IRIX 6.2) | B.1 | | |
| 7.4/P7.4-G94 – 7.4.1/P7.4.1-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.2) | B.1 | | |
| | Cray C90 (UNICOS 8.0.3) | D.4,E.1 | | |
| | Silicon Graphics IRIS-Power Challenge L R8000 (IRIX 6.2) | B.1 | | |
| 7.8/P7.8-G94 – 7.9.1/P7.9.1-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.2) | B.1 | | |
| | Cray C90 (UNICOS 8.0.3) | E.1 | | |
| | Silicon Graphics IRIS-Power Challenge L R8000 (IRIX 6.2) | D.4 | | |

| GAUSSRATE Version | Machine (Operating system) | GAUSSIAN Version | | |
|-------------------------------------|---|------------------|--------|------|
| | | 94 | 98 | 03 |
| 8.0/P8.0-G94 | | | | |
| | IBM RS/6000 model 550 (AIX 4.2) | B.1 | | |
| | IBM RS/6000 43P model 240 (AIX 4.3) | D.2 | | |
| | Silicon Graphics IRIS-Power Challenge L R10000 (IRIX 6.2) | D.4 | | |
| 8.1.1/P8.1-G94G98 – 8.2/P8.2-G94G98 | | | | |
| | IBM SP with 604e processor (AIX 4.3.1) | D.2 | A.7 | |
| | SGI-Origin 2000 with R10000 processor (IRIX 6.5) | D.4 | A.7 | |
| 8.6/P8.5.1-G94G98 | | | | |
| | SGI-Origin 2000 with R10000 processor (IRIX 6.5) | D.4 | | |
| 8.7/P8.7-G94G98 | | | | |
| | IBM SP with Power3 processor (AIX 4.3.4.0) | | A.11 | |
| | SGI Origin 2000 with R12000 processor (IRIX 6.5.12f) | | A.11 | |
| 8.9/P8.9-G94G98 – 9.0/P9.0-G94G98 | | | | |
| | IBM SP with Power3 processor (AIX 4.3.4.0) | | A.11 | |
| | SGI-Origin 2000 with R12000 processor (IRIX 6.5.12f) | E.2 | A.11 | |
| 9.1/P9.1-G03G98G94 | | | | |
| | IBM SP with Power3 processor (AIX 4.3.4.0) | | A.11 | B.01 |
| | SGI-Origin 2000 with R12000 processor (IRIX 6.5.12f) | E.2 | A.11 | B.01 |
| | Netfinity Linux Cluster with Pentium III (RedHat Linux 7.2) | | A.11.3 | B.01 |
| | SunBlade 2000 with UltraSparcIII processor (Solaris 8) | | A.11 | B.01 |

11. VERSION INFORMATION

11.1. GAUSSRATE version numbers

GAUSSRATE version numbers have the general form $x.y.z/Px'.y'.z'-Gx''$ where $x.y.z$ is the overall version number, $x'.y'.z'$ is the number of the version of POLYRATE on which it is based, and x'' is the number of the version of GAUSSIAN on which it is based. The part before the solidus, i.e., $x.y.z$, is unique, i.e., it changes if the interface changes, the POLYRATE version changes, or the GAUSSIAN version changes. Thus, the part after the solidus it is redundant information, and it may be omitted for simplicity if desired. In general, third-level revisions (z or z') are bug fixes (either to GAUSSRATE itself or to one or more of the codes interfaced by GAUSSRATE), and first and second level revisions (x,y,x' , or y') are enhancements.

Note: we sometimes update one or more of the manuals without updating the version number. The manual version is determined by the date of its most recent change and is given on its first page. Any changes other than the manual(s) always involve a change in version number of the code.

11.2. GAUSSRATE revision history

This section contains the revision history subsequent to version 7.1 (March 1997), which was the first version of the code.

Version 7.1.1/P7.1.1-G94 (March 1997)

1. A bug which caused the energy of the products (and therefore of the reverse rate constant) to be miscalculated for reactions with one product when the POLYRATE 7.1.1 methods were selected for the Hessian calculation optimization, and the GAUSSIAN 94 methods were selected for geometry optimizations has been fixed.
2. A bug which caused some restart calculations to abort when an atomic species is involved has been fixed.

Version 7.2/P7.2-G94 (April 1997)

1. The test runs have been modified to take account of changes in the new version of POLYRATE. This will lead to incompatibilities between the `fu5` input files for GAUSSRATE 7.1 and the `fu5` files for GAUSSRATE 7.2 if certain options are used. The user is advised to check Section 23.E of the POLYRATE 7.2 manual in order to modify the `fu5` input file from previous calculations. No incompatibilities are present in the `fu31` through `fu35` input files. The interface has not changed.
2. The compiling scripts have been modified in order to make the compilation cleaner and safer.

Version 7.3/P7.3-G94 (July 1997)

1. This version is based on a new version of POLYRATE. The test runs have been changed in order to use the new set of keywords and options. This will lead to incompatibilities between the `fu5` input files for previous versions of the program and the `fu5` files for GAUSSRATE 7.3 if certain options are used. The user is advised to check the Section 23.E of the POLYRATE 7.3 manual in order to modify the `fu5` input file from previous calculations.

2. The GAUSSRATE files have been renamed from `gr.#` to `esp.#`, for the sake of consistency with the POLYRATE and MORATE programs. Moreover, the numbering of these FORTRAN units was updated according to the new conventions established by POLYRATE 7.3; in particular, the files are assigned to FORTRAN units 71-76 instead of 31-36.
3. The input file `fu70` is now a case sensitive file. Hence, when typing UNIX path names, a capital letter in the path name must be entered as a capital letter, and a lower case letter must be entered as lower case.

Version 7.4/P7.4-G94 (August 1997)

1. This version is based on a new version of POLYRATE. The test runs have been modified in order to interface with POLYRATE 7.4, using the new keywords and options. These changes in POLYRATE will lead to incompatibilities between the `fu5` input files for previous versions of the GAUSSRATE program and the `fu5` files for GAUSSRATE 7.4 if certain options are used. The user is advised to check Section 23.E of the POLYRATE 7.4 manual in order to see whether it is necessary to modify the `fu5` input file from previous calculations.
2. Four new test runs for the CH₄OH system were added in order to illustrate the use of the STATUS keyword. In addition, some test runs were modified in order to apply the new POLYRATE capability for calculating vibrational frequencies by using redundant internal coordinates.
3. The code has been changed in order to interface with version E.1 of GAUSSIAN 94. Minor changes in the formatted checkpoint file written by GAUSSIAN make previous versions of GAUSSRATE incompatible with the E.1 revision of GAUSSIAN 94.

Version 7.4.1/P7.4.1-G94 (September 1997)

1. This version is based on a new version of POLYRATE. The interface between POLYRATE and GAUSSIAN has not changed. Please review the POLYRATE 7.4.1 revision history for details.

Version 7.8/P7.8-G94 (December 1997)

1. This version is based on a new version of POLYRATE. The user is advised to review section 23.D of the POLYRATE 7.8 manual to determine the possible incompatibilities in `fu5` input files from previous POLYRATE versions.
2. This update also involves the possibility of including wells along the reaction path. With this aim, files `esp.fu77` and `esp.fu78` have been included in the program.
3. The keywords GROPT and NOGROPT have been removed. The code now determines the optimization options automatically from the information in the `fu5` input file. This leads to incompatibilities with `esp.fu70` input files from older versions of the program.
4. A new test, `nh3ohtr1`, has been added to illustrate the use of the files `esp.fu77` and `esp.fu78` for calculating wells on the reaction path. Moreover, the test run `oh3tr2` has been modified in order to provide an example of the use of the RODS method.
5. Several minor modifications in the test runs have been introduced to reduce the timings.

Version 7.8.1/P7.8.1-G94 (February 1998)

1. This version is based on a new version of POLYRATE. The interface between POLYRATE and GAUSSIAN has not changed. Please review the POLYRATE 7.8.1 revision history for details.

Version 7.9/P7.9-G94 (March 1998)

1. This version is based on a new version of POLYRATE. The interface between POLYRATE and GAUSSIAN has not changed. The user is advised to review section 23.D of the POLYRATE 7.9 manual to determine the possible incompatibilities in `fu5` input files from previous POLYRATE versions.

Version 7.9.1/P7.9.1-G94 (April 1998)

1. This version is based on a new version of POLYRATE. The interface between POLYRATE and GAUSSIAN has not changed. Please review the POLYRATE 7.9.1 revision history for details.

Version 7.9.2/P7.9.2-G94 (June 1998)

1. A bug in the print out of the gradients of some stationary points after their optimization using GAUSSIAN 94 methods has been fixed. This bug fix involved changes in the *ohook* subroutine.

Version 8.0/P8.0-G94 (September 1998)

1. This version is based on a new version of POLYRATE. The FORTRAN source for the interface routines has not changed. Please review the POLYRATE 8.0 revision history for details. The test run input files have been updated to interface with POLYRATE 8.0. A new test run, *ch5tr2*, has been added to test the new ISPE method; and test run *oh3tr2* has been modified in order to use the new VRPE option for following the reaction path, allowing a larger step size.
2. A Korn shell script, *check*, has been included in the *testrun* directory to automatically compare the *ful5* output files obtained after running the test suite with those in the *testo* directory.
3. The structure of the distribution files and the compiling scripts have been modified in an attempt to make the compilation more straightforward. In addition, a compiling script for IBM computers with the 604e processor has been added.

Version 8.1.1/P8.1.1-G94G98 (July 1999)

1. This version is based on a new version of POLYRATE.
2. Modifications in the subroutine *goutsec* are added to make the interface work with a new version of GAUSSIAN (in particular, for GAUSSIAN 98 Rev. A.7). In this case, the

user only needs to indicate the directory of the GAUSSIAN 98 executable in the script `shuttle`.

3. The compilation script was modified to O3 with 64 bits for the IBM SP 604e processor.

Version 8.1.2/P8.1.2-G94G98 (August 1999)

1. This version is based on a new version of POLYRATE.

Version 8.2/P8.2-G94G98 (August 1999)

1. This version is based on a new version of POLYRATE.

Version 8.3/P8.3-G94G98 (December 1999)

1. This version is based on a new version of POLYRATE.

Version 8.4/P8.4-G94G98 (August 2000)

1. This version is based on a new version of POLYRATE.
2. A new keyword, RSTTOL, in the GENERAL section of input file `poly.fu70` has been added.
3. Modifications in the test suite were added in order to make all the test runs to run in a subdirectory of each test directory, so that the calculations are performed in a more clear fashion and the possibility of interfering with other GAUSSIAN or GAUSSRATE runs were minimized.
4. A new test run, `ch4ohtr6`, is added to test the LCG4 method for LCT tunneling.

Version 8.5/P8.5-G94G98 (October 2000)

1. This version is based on a new version of POLYRATE.

Version 8.6/P8.5.1-G94G98 (November 2000)

1. This version is based on a new version of POLYRATE.

Version 8.7/P8.7-G94G98 (October 2001)

1. This version is based on a new version of POLYRATE.

Version 8.9/P8.9-G94G98 (May 2002)

1. This version is based on a new version of POLYRATE.
2. The Korn shell script, `check`, has been renamed to `check94`. A new Korn shell script, `check98`, has been added to compare the `fu15` output files obtained after running the test suite with those in the `testo/g98` directory.
3. The SGI compilation script was modified to turn off some warnings during compilation.

Version 9.0/P9.0-G94G98 (May 2002)

1. This version is based on a new version of POLYRATE.

Version 9.1/P9.1-G03G98G94 (July 2003)

1. This version is based on a new version of POLYRATE.
2. This version allows interfacing POLYRATE with the GAUSSIAN 03 as well as GAUSSIAN 98 and GAUSSIAN 94. This new feature required modifications in the `shuttle` script and upgrading the `headr` subroutine. The distributed output files obtained by running GAUSSRATE with GAUSSIAN 03 are located in the new directory `testo/g03`. A new Korn shell script, `check03`, has been added to compare the `fu15` output files obtained after running the test suite with those in the `testo/g03` directory.
3. Test runs `ch4ohtr4`, `ch4ohtr5`, and `ch4ohtr6` were updated to include the new SPECSTOP keyword of POLYRATE.

4. The GAUSSRATE manual is now distributed as Word and pdf files instead of a txt file.
5. A few old variables that were not used anymore have been removed from the code.
6. The Cray platform is no longer supported. The `hooks_gr.cray` and `gaussrate.cray` files were removed.
7. The Sun and Linux platforms were added to the supported platforms. The `gaussrate.linux` and `gaussrate.sun` compiling scripts have been added in the `script` directory.

12. ACKNOWLEDGMENTS

The authors are grateful to Patton Fast for assistance in preparing GAUSSRATE and its documentation, and to Titus V. Albu for help in updating GAUSSRATE and its documentation. The development of GAUSSRATE has been supported in part by grants from the U.S. Department of Energy, Office of Basic Energy Sciences.